

## Performance Data – Filter

Model Number	Effective Filtration Area	Public Design Flow Rate*	Turnover (In Gallons)		Residential Design Flow Rate**	Turnover (In Gallons)	
			8 Hours	10 Hours		8 Hours	10 Hours
DE3620	36 ft. <sup>2</sup>	72 GPM	34,560	43,200	90 GPM	43,200	54,000
DE4820	48 ft. <sup>2</sup>	96 GPM	46,080	57,600	120 GPM	57,600	72,000
DE6020	60 ft. <sup>2</sup>	120 GPM	57,600	72,000	150 GPM	72,000	90,000
DE7220	72 ft. <sup>2</sup>	144 GPM	69,120	86,400	150 GPM	72,000	90,000

**NOTES:** \*Based on 2 GPM/ft.<sup>2</sup> (maximum allowable NSF rating).

\*\*Based on 2.5 GPM/ft.<sup>2</sup> (maximum allowable NSF rating).

## Performance Data – Valve Positions

Model Number	Filter	Backwash	Waste	Recirculate	Rinse	Closed
SP0425	•	•	•	•	—	—
SP0740DE	•	•	•	•	—	—
SP0710XR50	•	•	•	•	•	•
SP0715XR50	•	•	•	•	•	•
SP0410X502S	•	•	—	—	—	—
DE2400PAK2CS	•	—	—	—	—	—