

NOTES: All filters include pressure gauge, air relief valve and 1 ½" drain plug.

*Above dimensions are for filter only. Add 12" for 1 ½" and 14" for 2" multiport valves. Add 7" for 2" slide valve.

Model Number	Description	Pipe Size	Valve Positions	Ctn. Qty.	Ctn. Weight
Valve and Coupling Selections					OPEN LINE
SP0425	SelectaFlo	2" SKT x 2 ½" SLIP	4	1	12 lbs.
SP0740DE	SelectaFlo	2" SKT	4	1	9 lbs.
SP0710XR50	VariFlo	1 ½" FIP	6	1	6 lbs.
SP0715XR50	VariFlo	2" FIP	6	1	9 lbs.
SP0410X502S	Slide Valve	2" SKT	2	1	4 lbs.
DE2400PAK2CS	Coupling	1 ½" SKT x 2" SLIP	—	10	10 lbs.

Performance Data – Filter

Model Number	Effective Filtration Area	Design Flow Rate*	Turnover	
			8 Hours	10 Hours
DEP60	60 ft ² / 5.5 m ²	120 GPM / 454 LPM	57,600 gal / 218 kl	72,000 gal / 273 kl
DEP80	80 ft ² / 7.4 m ²	150 GPM / 568 LPM	72,000 gal / 273 kl	90,000 gal / 341 kl
DEP100	100 ft ² / 9.3 m ²	150 GPM / 568 LPM	72,000 gal / 273 kl	90,000 gal / 341 kl

NOTE: *2" piping is recommended for flow rates equal to or greater than 90 GPM (341 LPM). Hayward® doesn't recommend flow rates above 150 GPM.